


**PDC Elastomer Lined Series 27
Butterfly Valve
2" thru 36" for
125/150 lb. Flanging**



How To Order

*Material Option Followed By an Asterisk, May Not be Routinely Carried in Inventory, and May Result in Longer Deliveries Than Normal.

Use the following table to determine your part number:

Example: to code an 8 " wafer style butterfly valve with cast iron body, aluminum bronze disc, EPDM seat, 416 stainless steel shaft, bronze bushing, 10 position lock lever and no special configuration would be coded as follows:

27-0080-W-1-1-1-1-2-1

When "Special" materials are selected, be sure to completely describe on purchase order.

Please provide the following information:

- **Flow Media**
- **Operating Temperature F°**
- **No. of [open/close] cycles/day**
- **Line Pressure (PSIG) = _____.**
- **Delta P = _____.**

Valve Series 27

| Nominal Size Code | Body Style | Body Material | Disc Material | Seat Material | Stem/Bushing Material | Operators | Special Configuration |
|-------------------|------------|-----------------|-------------------------------|---------------|-----------------------|----------------------------|--------------------------|
| 0020= 2" | W = Wafer | 1= Cast Iron | 1= Alum. Bronze | 1= EPDM | 1= 416 S/S w/ Bronze | 1= None | 1= Leave Blank |
| 0030= 3" | L = Lug | 2= Ductile Iron | 2= Nickle Plated Ductile Iron | 2= Buna-N | 2= 316 S/S w/ Bronze | 2= 10 Position Lock Lever | 2= 50 PSI Under Cut Disc |
| 0040= 4" | | 3 = 316 S/S | 3 = 316 S/S | 3= Viton | 3= 316 S/S w/ Tef | 3= Gear Operator | X7 = Special |
| 0060= 6" | | X1 = Special | X2 = Special | X3 = Special | 4= 316 S/S w/ Tef | 4= Double Acting Pneumatic | |
| 0080= 8" | | | | | X4 = Special | 5= Electric | |
| 0100= 10" | | | | | | 6= Spring return Pneumatic | |
| 0120= 12" | | | | | | X5 = Special | |
| 0140= 14" | | | | | | | |
| 0160= 16" | | | | | | | |
| 0180= 18" | | | | | | | |
| 0200= 20" | | | | | | | |
| 0240 = 24" | | | | | | | |
| 0300 = 30" | | | | | | | |
| 0360 = 36" | | | | | | | |

Process Development & Control, Inc. reserves the right to make design improvements and/or change dimensions without notice.